



- Frame Size: 20.5*12*11mm
- Plunger: $\phi 4$
- Power : 1.2-12W
- Voltage: DC6-48V
- Current: 0.1-2A
- Stroke: 0-5mm
- Force: 0-250gf
- Move Type: Pull
- Life Expectancy: >100K cycles

duty cycle=100% x $\frac{\text{"on" time}}{\text{"on" time} + \text{"off"}}$	100%	50%	25%	10%
	continuous	intermittent		
Max. "on" time in seconds	∞	50	18	2
watts at 20°C	1.2	2.4	4.8	12
type no. (** : resistance)	(volts DC) resistance $\Omega \pm 10\%$ at 20°C			
SDO-0420L-06A**	(6V) 30	(6V) 15	(6V) 7.5	(6V) 3
SDO-0420L-12A**	(12V) 120	(12V) 60	(12V) 30	(12V) 12
SDO-0420L-24A**	--	(24V) 240	(24V) 120	(24V) 45
SDO-0420L-48A**	--	--	--	(48V) 192

SHENZHEN ZANTY ELECTRONICS CO., LTD.

Address: 4th Floor, Building 1, Lianchuang Science and Technology Park, No. 21 Bulan Road, Nanwan Street, Longgang District, Shenzhen, Guangdong, China

Email: sales@zanty.com

Website: www.zanty.com