



- Frame Size: 20*16*13mm
- Plunger: ϕ 5.0
- Power : 1.6-16W
- Voltage: DC6-48V
- Current: 0.13-2.67A
- Stroke: 0-4mm
- Force: 0-700gf
- Move Type: Push
- Life Expectancy: >1000K cycles

duty cycle=100% x $\frac{\text{"on" time}}{\text{"on" time} + \text{"off"}}$	100%	50%	25%	10%
Max. "on" time in seconds	∞	55	19	3
watts at 20°C	1.6	3.2	6.4	16
type no. (** : resistance)	(volts DC) resistance $\Omega \pm 10\%$ at 20°C			
SDO-0520S-06A**	(6V) 22.5	(6V) 11.3	(6V) 5.6	(6V) 2.2
SDO-0520S-12A**	(12V) 90	(12V) 45	(12V) 22.5	(12V) 9
SDO-0520S-24A**	--	(24V) 180	(24V) 90	(24V) 36
SDO-0520S-48A**	--	--	--	(48V) 144

SHENZHEN ZANTY ELECTRONICS CO., LTD.

Address: 4th Floor, Building 1, Lianchuang Science and Technology Park, No. 21 Bulan Road, Nanwan Street, Longgang District, Shenzhen, Guangdong, China

Email: sales@zanty.com

Website: www.zanty.com