



- Frame Size: 15.5*22*19mm
- Plunger: ϕ 6.1
- Power : 3-25W
- Voltage: DC6-48V
- Current: 0.06-4.16A
- Stroke: 0-5mm
- Force: 0-500gf
- Move Type: Push
- Life Expectancy: > 200K cycles

duty cycle=100% x $\frac{\text{"on" time}}{\text{"on" time} + \text{"off"}}$	100%	50%	25%	10%
Max. "on" time in seconds	∞	50	12	2
watts at 20°C	3	6	10	25
type no. (** : resistance)	(volts DC) resistance $\Omega \pm 10\%$ at 20°C			
SDO-0615S-06A**	(6V) 12	(6V) 6	(6V) 3.6	(6V) 1.44
SDO-0615S-12A**	(12V) 48	(12V) 24	(12V) 14.4	(12V) 5.76
SDO-0615S-24A**	(24V) 192	(24V) 96	(24V) 57.6	(24V) 23.04
SDO-0615S-48A**	(48V) 768	(48V) 384	(48V) 230.4	(48V) 92.16

SHENZHEN ZANTY ELECTRONICS CO., LTD.

Address: 4th Floor, Building 1, Lianchuang Science and Technology Park, No. 21 Bulan Road, Nanwan Street, Longgang District, Shenzhen, Guangdong, China

Email: sales@zanty.com

Website: www.zanty.com