



- Frame Size: 28.5*20*16mm
- Plunger: $\phi 6.0$
- Power : 3-30W
- Voltage: DC6-48V
- Current: 0.06-5A
- Stroke: 0-6mm
- Force: 0-700gf
- Move Type: Pull
- Life Expectancy: > 1500K cycles

duty cycle=100% x $\frac{\text{"on" time}}{\text{"on" time} + \text{"off"}}$	100%	50%	25%	10%
Max. "on" time in seconds	∞	55	19	3
watts at 20°C	3	8	12	30
type no. (** : resistance)	(volts DC) resistance $\Omega \pm 10\%$ at 20°C			
SDO-0628L-06A**	(6V) 12	(6V) 4.5	(6V) 3	(6V) 1.2
SDO-0628L-12A**	(12V) 48	(12V) 18	(12V) 12	(12V) 4.8
SDO-0628L-24A**	(24V) 192	(24V) 72	(24V) 48	(24V) 19.2
SDO-0628L-48A**	(48V) 768	(48V) 288	(48V) 192	(48V) 76.8

SHENZHEN ZANTY ELECTRONICS CO., LTD.

Address: 4th Floor, Building 1, Lianchuang Science and Technology Park, No. 21 Bulan Road, Nanwan Street, Longgang District, Shenzhen, Guangdong, China

Email: sales@zanty.com

Website: www.zanty.com