



- Frame Size: 26\*25\*22mm
- Plunger:  $\phi$  8.1
- Power : 2.4-24W
- Voltage: DC6-48V
- Current: 0.05-4A
- Stroke: 0-6mm
- Force: 0-1300gf
- Move Type: Pull
- Life Expectancy: > 800K cycles

duty cycle=100% x $\frac{\text{"on" time}}{\text{"on" time} + \text{"off"}}$	100%	50%	25%	10%
Max. "on" time in seconds	$\infty$	50	19	3
watts at 20°C	2.4	4.8	9.6	24
type no. ( ** : resistance)	(volts DC) resistance $\Omega \pm 10\%$ at 20°C			
SDO-0826L-06A**	(6V) 15	(6V) 7.5	(6V) 3.75	(6V) 1.5
SDO-0826L-12A**	(12V) 60	(12V) 30	(12V) 15	(12V) 6
SDO-0826L-24A**	(24V) 240	(24V) 120	(24V) 60	(24V) 24
SDO-0826L-48A**	(48V) 960	(48V) 480	(48V) 240	(48V) 96

## SHENZHEN ZANTY ELECTRONICS CO., LTD.

Address: 4th Floor, Building 1, Lianchuang Science and Technology Park, No. 21 Bulan Road, Nanwan Street, Longgang District, Shenzhen, Guangdong, China

Email: [sales@zanty.com](mailto:sales@zanty.com)

Website: [www.zanty.com](http://www.zanty.com)